



SECTION I: PRODUCT INFORMATION

PRODUCT: SikaTack®-Ultrafast // REVISION DATE: February 24<sup>th</sup>, 2015

USAGE: ONE COMPONENT URETHANE BASED ADHESIVE FOR WINDSHIELD

SUPPLIER: SIKA CANADA INC.
601, avenue Delmar
Pointe Claire, QC
H9R 4A9

EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666

TDG CLASSIFICATION: Not regulated WHMIS Classification: D2A
UN NUMBER: Not established Class: Not applicable
Packaging Group: Not applicable

SECTION II: HAZARDOUS INGREDIENTS

Table with 6 columns: Hazardous ingredients, %, T.L.V., # CAS, LD50 (mg/kg) (route, species), LC50 (species, route). Rows include POLYOL AND ISOCYANATE PREPOLYMER, CARBON BLACK, METHYLENE BIS PHENYL ISOCYANATE.

SECTION III: PHYSICAL CHARACTERISTICS

Table with 2 columns for Physical State and Appearance and Odor, and Boiling Point, Freezing Point, Density, Water Solubility, pH, % volatile, Water/Oil Distribution.



PRODUCT: SikaTack®-Ultrafast //

SECTION IV: FIRE AND EXPLOSION HAZARDS

Flammability: No  
 If Yes, under what conditions:  
 Extinguishing methods: Foam, dry chemical products, CO<sub>2</sub>, water for large flames.  
 Special Methods: Firefighters must wear complete protective clothing with respiratory equipment and they must protect any exposed skin. Heated isocyanates react strongly with water.

TDG inflammability Class: Not regulated  
 Flammable upper limits (% vol.): Not Established  
 Flammable lower limits (% vol.): Not Established  
 Flash Point (method used): > 101°C  
 Auto-ignition temperature: Not Established  
 Dangerous Combustion Products: Carbon oxides, Nitrogen oxide.  
 Protect from mechanical impact: No  
 Protect from static discharge: No

SECTION V: REACTIVITY DATA

Chemical stability: Yes  
 If not, under what conditions:  
 Incompatibility with other material: Yes  
 If Yes, which ones: Acid, strong oxidizer, amine.

Dangerous decomposition products: Carbon oxides, Nitrogen oxide.  
 Polymerization Risks: No



PRODUCT: SikaTack®-Ultrafast //

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes: Irritating

Skin: Irritating. Contact may result in dermatitis, allergic reactions, and sensitization.

Inhalation: Vapor or mist from this product may cause irritation.

Ingestion: May cause nausea, vomiting, fainting, diarrhea, lung damage, G.I. system disorder, constipation.

Carcinogenicity: Carbon Black is a possible carcinogen (according to the IARC)

Toxic effects on reproduction: Not Established

Teratogenicity: Not Established

Mutagenicity: Not Established

Product with synergistic effects: Not Established

Over exposure may cause breathing difficulties, sensitization, headaches, nausea, vomiting. May aggravate respiratory, skin, eye, lung problems and allergies.

If the product is applied according to the manufacturer none of these symptoms should be encountered.

A person who is sensitized to isocyanate may have a reaction with a level of isocyanate well below the T.L.V.

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems. An over exposure may cause death.



PRODUCT: **SikaTack®-Ultrafast //**

**SECTION VII: PREVENTIVE MEASURES**

**PERSONAL PROTECTIVE EQUIPMENT**

Gloves: Use chemical resistant gloves.  
Respiratory equipment: Not necessary under normal use.  
Eyes: Full-face mask or safety glasses  
Shoes: Leather  
Clothing: Rubber Apron  
Other: Eye wash station, shower

**OTHERS**

Ventilation: Sufficient ventilation required  
Procedure in case of leaks: Absorb with sand or other absorbent material.  
Handling and Equipment methods: Avoid skin, eye and clothing contact  
Warehouse Requirements: Keep all containers closed in a cool, dry and well ventilated area. Keep away from heat and open flame.  
Special Shipping Instructions: See TDG class  
Waste Disposal: Dispose of sand and rinse water according to municipal, provincial or federal laws for disposal of chemicals.



PRODUCT: SikaTack®-Ultrafast //

## SECTION VIII: FIRST AID

- Skin : Remove contaminated clothing and shoes.  
Wash immediately with plenty of water.  
Wash clothing before re-wearing.  
Consult a physician if required.
- Eyes : Rinse eyes immediately with plenty of water for several minutes, while holding eyelids wide open, to ensure a proper wash.  
See a physician immediately.
- Inhalation : In the case of overexposure, evacuate to fresh air.  
Consult a physician if required.
- Ingestion : Drink plenty of water. Do not induce vomiting.  
Do not give anything by mouth to an unconscious person.  
See a physician immediately.

## SECTION IX: PREPARATION INFORMATION

Prepared By: R & D of Sika Canada Inc.  
Telephone #: (514) 697-2610  
Fax #: (514) 694-2792

**Notice To Reader**

*The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section IX of this MSDS.*

**SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

*All sales of Sika products are subject to its current terms and conditions of sale available at [www.sika.ca](http://www.sika.ca) or 514-697-2610.*