



SECTION I: PRODUCT INFORMATION

PRODUCT: **Sikaflex®-220+** (MSDS #604239) REVISION DATE: January 15th, 2015

USAGE: ONE COMPONENT URETHANE BASED ADHESIVE

MANUFACTURER/SUPPLIER: SIKA CANADA INC.
601, avenue Delmar
Pointe Claire, QC
H9R 4A9

EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666

TDG CLASSIFICATION: Not Regulated WHMIS Classification: B3, D2A
UN NUMBER: Not Established Class: Not Applicable
Packaging Group: Not Applicable

SECTION II: HAZARDOUS INGREDIENTS

| Hazardous ingredients | % | T.L.V. | # CAS | LD ₅₀ (mg/kg) (route, species) | LC ₅₀ (species, route) |
|--|-------|--|---------------|--|--------------------------------------|
| CALCIUM OXIDE | 1-5 | Not Available | 1305-78-8 | Not Available | Not Available |
| XYLENE | 1-5 | ACGIH 100ppm (TWA) 150ppm (STEL) | 1330-20-7 | 4300 (oral, rat) | 6350ppmh/4H (rat) |
| POLYOL AND ISOCYANATE PREPOLYMER | 30-60 | Not Established | Not Available | Not Established | Not Established |
| CARBON BLACK | 10-30 | 3.5 mg/m ³ (TWA) | 1333-86-4 | 15 400 (oral, rat) | Not established |
| AMORPHOUS SILICA | 1-5 | Not Established | 7631-86-9 | Not Established | Not Established |
| METHYLENE BISPHENYL ISOCYANATE | 0.1-1 | ACGIH 0,005 ppm | 101-68-8 | 31 600 (oral, rat) | 369mg/m ³ /4H (rat) |
| | | | | | |
| | | | | | |
| | | | | | |

SECTION III: PHYSICAL CHARACTERISTICS

| | | | |
|----------------------|---------------------------|-------------------------|-----------------|
| Physical State: | Paste | Boiling Point: | Not Established |
| Appearance and Odor: | Aromatic odor black paste | Freezing Point: | Not Established |
| Odor Threshold: | Not Established | Density: | 1,2 g/ml |
| Evaporation Rate: | Not Established | Water Solubility: | Not Established |
| Vapor Density: | Not Established | pH: | Not Established |
| Vapor Pressure: | Not Established | % volatile: | < 5 |
| | | Water/Oil Distribution: | Not Established |



PRODUCT: Sikaflex®-220+

MSDS #604239

SECTION IV: FIRE AND EXPLOSION HAZARDS

Flammability: Combustible
 If Yes, under what conditions: Flame, spark
 Extinguishing methods: Foam, dry chemical products, CO₂, water for large flames.
 Special Methods: Firefighters must wear complete protective clothing with respiratory equipment and they must protect any exposed skin. Heated isocyanates react strongly with water.

TDG inflammability Class: Not Regulated
 Flammable upper limits (% vol.): Not Established
 Flammable lower limits (% vol.): Not Established
 Flash Point (method used): > 80°C
 Auto-ignition temperature: Not Established
 Dangerous Combustion Products: Carbon oxides, Aldehydes, Ketones, HCL, Nitrogen Oxide, IPDI, MDI
 Protect from mechanical impact: No
 Protect from static discharge: No

SECTION V: REACTIVITY DATA

Chemical stability: Yes
 If not, under what conditions
 Incompatibility with other material: Yes
 If Yes, which ones: Acid, strong oxidizer, amine

Dangerous decomposition products: Carbon oxides, Aldehydes, Ketones, HCL, Nitrogen Oxide, IPDI, MDI
 Polymerization Risks: No



PRODUCT: Sikaflex®-220+

MSDS #604239

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes: Irritating.

Skin: Irritating. Contact may result in dermatitis, allergic reactions, and sensitization.

Inhalation: Vapor or mist from this product may cause irritation.

Ingestion: May cause nausea, vomiting, fainting, diarrhea, lung damage, gastro-intestinal system disorder, constipation, ulcers.

Carcinogenicity: Carbon black is possibly carcinogen according to the IARC.

Toxic effects on reproduction: Not Established

Teratogenicity: Xylene is classified as a development toxicant (Embryo toxin).

Mutagenicity: Not Established

Product with synergistic effects: Not Established

Over exposure may cause breathing difficulties, sensitization, headaches, nausea, vomiting. May aggravate respiratory, skin, eye, lung problems and allergies.

If the product is applied according to the manufacturer, none of these symptoms should be encountered.

A person who is sensitized to isocyanate may have a reaction with a level of isocyanate well below the T.L.V.

Xylene is a central nervous system depressor and in rare cases, may cause a sensitization of the heart muscle causing arrhythmia.

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems. An over exposure may cause death.



PRODUCT: Sikaflex®-220+

MSDS #604239

SECTION VII: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

Gloves: Use chemical resistant gloves.

Respiratory equipment: Not necessary under normal use.

Eyes: Full-face mask or safety glasses

Shoes: Leather

Clothing: Rubber Apron

Other: Eye wash station, shower

OTHERS

Ventilation: Sufficient ventilation required

Procedure in case of leaks: Absorb with sand or other absorbent material.

Handling and Equipment methods: Avoid skin, eye and clothing contact

Warehouse Requirements: Keep all containers closed in a cool, dry and well ventilated area. Keep away from heat and open flame.

Special Shipping Instructions: See TDG class

Waste Disposal: Dispose of sand and rinse water according to municipal, provincial or federal laws for disposal of chemicals.



PRODUCT: Sikaflex®-220+

MSDS #604239

SECTION VIII: FIRST AID

- Skin : Remove contaminated clothing and shoes.
Wash immediately with plenty of water.
Wash clothing before re-wearing.
Consult a physician if required.
- Eyes : Rinse eyes immediately with plenty of water for several minutes, while holding eyelids wide open, to ensure a proper wash.
See a physician immediately.
- Inhalation : In the case of overexposure, evacuate to fresh air.
Consult a physician if required.
- Ingestion : Drink plenty of water. Do not induce vomiting.
Do not give anything by mouth to an unconscious person.
See a physician immediately.

SECTION IX: PREPARATION INFORMATION

Prepared By: R & D of Sika Canada Inc.
 Telephone #: (514) 697-2610
 Fax #: (514) 694-2792

Notice To Reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section IX of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.